Flexi**Draft™ FRIDGE**

UNDERCOUNTER 20







DEDICATED TO DRAFT QUALITY



FlexiDraft[™] FRIDGE

UNDERCOUNTER 20

INSIGHT

The UNDERCOUNTER 20 fridge is prepared to be integrated into an existing bar setup and combines all the benefits of a full branded $FlexiDraft^{T}$ font with an accurate, energy efficient and eco-friendly fridge.

Flexi**Draft**^m UNDERCOUNTER 20 is include pre-drilled holes for external CO₂ supply and are available with a range of optional accessories including keg slider function, interior lighting and door lock.

The Flexi**Draft**[™] UNDERCOUNTER is designed to the use of the industry standard sized 20, 30 and 50 l kegs. Flexi**Draft**[™] UNDERCOUNTER 20 can be specified with 1 or 2 fonts and comes with adjustable legs for perfect fit.

KEG CONFIGURATION (EXAMPLES)





FEATURES AND BENEFITS

- · Prepared for font illumination
- Adjustable legs

SPECIFICATIONS FlexiDraft [™] UND	

Number of fonts	1-2 fonts
Cooling:	
Power of compressor	110V: 491 watt - 230V: 406 watt
Coolant type	R290
Coolant amount	50 g
Performance:	
Ambient temperatur max	40°C
Cooling temperature	2°-4°C
Electrical:	
Main supply/ Run current	110V - 60Hz / 4,3A - 230V - 50/60Hz / 2,2A
Plug compatability	Type A, B, C, F, G, H, I, J, K, L, M, N, O
Energy consumption (at 24°C ambient temp.)	2,4 kWh/24h
Noise level:	
Specification	48-55 db (A), 0,5 m from the cooler
Dimensions of cooler:	
Width	Outside: 920 mm - Inside: 590 mm
Depth	Outside: 610 mm - Inside: 510 mm
Height (incl. legs)	Outside: 870-885 mm - Inside: 755 mm
Weight	76 kg
Legs	Adjustable height 15-30 mm